

MARK J. EDSALL, P.E., P.P. (NY, NJ & PA) MICHAEL W. WEEKS, P.E. (NY, NJ & PA) MICHAEL J. LAMOREAUX, P.E. (NY, NJ, PA, VT, VA & CT) PATRICK J. HINES LYLE R. SHUTE, P.E. LEED-AP (NY, NJ, PA)

Main Office 33 Airport Center Drive Suite 202 New Windsor, New York 12553

(845) 567-3100 fax: (845) 567-3232

e-mail: mheny@mhepc.com

Principal Emeritus: RICHARD D. McGOEY, P.E. (NY & PA) WILLIAM J. HAUSER, P.E. (NY, NJ & PA)

TOWN OF NEWBURGH PLANNING BOARD **TECHNICAL REVIEW COMMENTS** 

PROJECT: **SERVISS 4 LOTSUBDIVISION** 

PROJECT NO.: 19-10

PROJECT LOCATION: SECTION 34, BLOCK 1, LOT 25.2

**REVIEW DATE: 27 SEPTEMBER 2019 MEETING DATE: 03 OCTOBER 2019** 


PROJECT REPRESENTATIVE: JAMES A. DILLIN, PLS/TALCOTT ENGINEERING


- 1. Response from Highway Superintendent regarding driveway location should be received.
- 2. Common driveway access and maintenance agreement is required for lots 2 & 3 for the shared driveway.
- 3. The plans contains a roadway dedication parcel 25 feet from the centerline of Union Avenue. Roadway dedication information should be provided to the Planning Board Attorney's office for review.


Respectfully submitted,

McGoey, Hauser and Edsall Consulting Engineers, D.P.C.

Patrick J. Hines Principal







#### SEPTIC SYSTEM GENERAL NOTES:

- 1. ALL PORTIONS OF THE SEPTIC FIELD WILL BE A MINIMUM DISTANCE OF 200 FEET UP SLOPE AND 100 FEET DOWN SLOPE FROM ANY WELL
- 2. SEPTIC TANK TO BE LOCATED A MINIMUM DISTANCE OF 10 FEET FROM
- ANY BUILDING OR PROPERTY LINE AND 50' FROM WELL. CELLAR DRAINS, ROOF DRAINS OR FOOTING DRAINS SHALL NOT BE
- DISCHARGED IN OR INTO THE VICINITY OF ABSORPTION FIELD. 4. NO SWIMMING POOLS, DRIVEWAYS, OR STRUCTURES THAT MAY COMPACT THE SOIL
- SHALL BE CONSTRUCTED OVER ANY PORTION OF THE ABSORPTION FIELD.
- 5. NO TRENCHES TO BE INSTALLED IN WET SOIL.

8. DISTRIBUTION LINES ARE TO BE CAPPED.

- 6. RAKE SIDES AND BOTTOM OF TRENCH PRIOR TO PLACING GRAVEL IN
- ABSORPTION TRENCH. GROUT ALL PIPE PENETRATIONS TO CONC. SEPTIC TANK & DISTRIBUTION BOX.
- THE PERIMETER OF THE ABSORPTION FIELD SHOULD BE GRADED TO DIVERT
- SURFACE WATER. 10. ALL NEWLY DISTURBED AREAS SHALL BE IMMEDIATELY STABILIZED UPON CONSTRUCTION COMPLETION USING GRASS SEED & MULCH.
- 11. NO SEWAGE SYSTEM SHALL BE PLACED WITHIN 100' OF ANY WATER COURSE OR 35' DRAINAGE DITCH.
- 12. ALL LAUNDRY AND KITCHEN WASTES SHALL BE DISCHARGED INTO SEWAGE
- 13. BENDS SHALL BE USED WHEN ENTRANCE OR EXIT FROM SEPTIC TANK IS
- NOT APPROXIMATELY STRAIGHT. IF BENDS ARE USED AT POINTS OTHER THAN ENTRANCE OR EXIT POINTS, THEN A CLEANOUT IS REQUIRED. 14. THE DESIGN AND LOCATION OF THE SANITARY FACILITIES SHALL NOT BE
- CHANGED WITHOUT RESUBMISSION FOR APPROVAL 15. HEAVY EQUIPMENT SHALL BE KEPT OFF THE AREA OF THE ABSORPTION FIELDS EXCEPT DURING THE ACTUAL CONSTRUCTION. THERE SHALL BE
- NO UNNECESSARY MOVEMENT OF CONSTRUCTION EQUIPMENT IN THE ABSORPTION FIELD AREA BEFORE, DURING, OR AFTER CONSTRUCTION 16. THIS SYSTEM WAS NOT DESIGNED TO ACCOMMODATE GARBAGE GRINDERS, JACUZZI TYPE SPA TUBS OVER 100 GALLONS, OR WATER CONDITIONERS AS SUCH, THESE ITEMS SHALL NOT BE INSTALLED UNLESS THE SYSTEM
- IS REDESIGNED TO ACCOUNT FOR THESE. 17. THERE MUST BE AN UNINTERRUPTED POSITIVE SLOPE FROM THE SEPTIC TANK (OR ANY PUMPING OR DOSING CHAMBER) TO THE HOUSE, ALLOWING
- SEPTIC GASES TO DISCHARGE THROUGH THE STACK VENT. 18. THE PURCHASER OF THIS LOT SHALL BE PROVIDED WITH A COPY OF THE
- APPROVED PLANS AND AN ACCURATE AS-BUILT DRAWING OF ANY EXISTING SANITARY FACILITIES.
- 19. THE DESIGN ENGINEER WILL BE REQUIRED TO CERTIFY THE COMPLETED DISPOSAL FACILITY.
- 20. AN ASBUILT SURVEY AND CERTIFICATION SHALL BE PROVIDED TO THE TOWN OF NEWBURGH CODE ENFORCEMENT DEPARTMENT PRIOR TO ISSUANCE OF A CERTIFICATION OF OCCUPANCY.

### STANDARD NOTES.

THE DESIGN, CONSTRUCTION AND INSTALLATION SHALL BE IN ACCORDANCE WITH THIS PLAN AND GENERALLY ACCEPTED STANDARDS IN EFFECT AT THE TIME OF CONSTRUCTION WHICH INCLUDE:

"APPENDIX 75-A, WASTE TREATMENT - INDIVIDUAL HOUSEHOLD SYSTEMS, NFW YORK STATE SANITARY CODE." "WASTE TREATMENT HANDBOOK, INDIVIDUAL HOUSEHOLD SYSTEMS, NEW YORK STATE DEPARTMENT OF HEALTH."

"RURAL WATER SUPPLY, NEW YORK STATE DEPARTMENT OF HEALTH." "PLANNING THE SUBDIVISION AS PART OF THE TOTAL ENVIRONMENT, NEW YORK STATE DEPARTMENT OF HEALTH.

"THIS PLAN IS APPROVED AS MEETING THE APPROPRIATE AND APPLIED TECHNICAL STANDARDS, GUIDELINES, POLICIES AND PROCEDURES FOR ARRANGEMENT OF SEWAGE DISPOSAL AND TREATMENT AND WATER SUPPLY FACILITIES.

ALL WELLS AND S.D.S. EXISTING OR APPROVED WITHIN 200' OF THE PROPOSED WELLS AND S.D.S. ARE SHOWN ON THIS PLAN ALONG WITH ANY OTHER ENVIRONMENTAL HAZARDS IN THE AREA THAT MAY AFFECT THE DESIGN AND FUNCTIONAL ABILITY OF THE S.D.S. AND WELL. IT SHALL BE DEMONSTRATED BY THE CONTRACTOR TO THE CERTIFYING ENGINEER THAT THE SEPTIC TANK IS SEALED, WATER TIGHT AND ACCEPTABLE

FOR USE. THIS SHALL REQUIRE, AS A MINIMUM, THE FILLING OF THE TANK WITH WATER TO OBSERVE IF IT IS IN FACT SEALED, WATERTIGHT AND ACCEPTABLE FOR USE.

ALL PROPOSED WELLS AND SERVICE LINES ON THIS PLAN ARE ACCESSIBLE FOR INSTALLATION AND PLACEMENT.

TRENCH BOTTOMS TO BE SET LEVEL AND PARALLEL TO EXISTING CONTOURS. MAXIMUM DEPTH OF USABLE FILL PLUS 6" OF TOPSOIL SHALL NOT EXCEED 30".

> TOWN OF NEWBURGH PROJECT # 19-10 THIS SHEET IS INVALID AND VOID UNLESS ACCOMPANIED BY REMAINING SHEETS IN SET.

	REV.:	DATE:	BY:	DESCRIPTION:
	2	8/08/19	RBM	RELOCATED LOT 3 SEPTIC
	1	07/02/19	RBM	RELOCATED LOT 3 SEPTIC
TALCOTT ENGINEERING DESIG				
1 GARDNERTOWN ROAD NEWBURGH, NY 12550 (845)-569-8400				

REVISIONS


### T 3 SEPTIC DESIGN PLLC

(FAX)(845)-569-4583 TALCOTTDESIGN12@GMAIL.COM


SUBDIVISION OF PROPERTY FOR **SERVISS** UNION AVENUE, SBL:34-1-25.2


TOWN OF NEWBURG. ORANGE COUNTY NY

SHEET NUMBER 18288-HSS 3 OF 4 NTS CHARLES T. BROWN.P.E. 05/17/18



### SILT FENCE DETAILS





CONSTRUCTION NOTES FOR FABRICATED SILT FENCE

POSTS: STEEL EITHER T OR U TYPE

6" MAX. MESH OPÉNING

APPROVED EQUAL

GEOFAB, ENVIROFENCE, OR APPROVED EQUAL


FILTER CLOTH: FILTER X, MIRAFI 100X, STABILINKA T140N OR

OR 2" HARDWOOD

FENCE: WOVEN WIRE, 14 1/2 GA.

- 1. WOVEN WIRE FENCE TO BE FASTENED SECURELY TO FENCE POST WITH WIRE TIES OR STAPLES.
- 2. FILTER CLOTH TO BE FASTENED SECURELY TO WOVEN WIRE FENCE WITH TIES SPACED EVERY 24" AT TOP AND MID SECTION.
- 3. WHEN TWO SECTIONS OF FILTER CLOTH ADJO EACH OTHER THEY SHALL BE OVERLAPPED B
- 6" AND FOLDED.4. MAINTENANCE SHALL BE PERFORMED AS NEE
  - ICE SHALL BE PERFORMED AS NEEDED RIAL REMOVED WHEN "BULGES" DEVELOF T FENCE.

#### STABILIZED CONSTRUCTION ENTRANCE



NOTE: ENTRANCE SHALL BE MAINTAINED AS CONDITIONS DEMAND TO PREVENT TRACKING OF SEDIMENT ONTO PUBLIC RIGHT OF WAYS

ALL SEDIMENTATION STRUCTURES WILL BE INSPECTED AND MAINTAINED ON A REGULAR BASIS. A CRUSHED STONE, VEHICLE WHEEL-CLEANING BLANKET WILL BE INSTALLED WHENEVER A CONSTRUCTION ACCESS ROAD INTERSECTS ANY PAVED ROADWAY. SAID BLANKET WILL BE COMPOSED OF 6" DEPTH OF 1"-1 1\2" CRUSHED STONE, WILL BE AT LEAST 30' X 50' AND SHOULD BE PLACED ON COMPACTED SUBGRADE AND SHALL BE MAINTAINED.

ALL DRIVEWAYS MUST BE STABILIZED WITH 1"-1 1\2" CRUSHED STONE OR SUB-BASE PRIOR TO

INDIVIDUAL HOME CONSTRUCTION.


PAVED ROADWAYS MUST BE KEPT CLEAN AT ALL TIMES.

ALL CATCH BASIN INLETS WILL BE PROTECTED WITH A CRUSH STONE OR HAYBALE FILTER (FILTER DETAILS APPEAR ON PLAN).

ALL STORM DRAINAGE OUTLETS WILL BE STABILIZED, AS REQUIRED, BEFORE DISCHARGE POINTS BECOME OPERATIONAL.

ALL SOIL EROSION AND SEDIMENT CONTROL STRUCTURES MUST BE DETAILED ON THE PLAN.

LOT #4




## TOWN OF NEWBURGH WATER SYSTEM NOTES:


- CONSTRUCTION OF POTABLE WATER UTILITIES AND CONNECTION TO THE TOWN OF NEWBURGH WATER SYSTEM REQUIRES A PERMIT FROM THE TOWN OF NEWBURGH WATER DEPARTMENT. ALL REQUIREMENTS SHALL CONFORM TO THE REQUIREMENTS OF THE NEW YORK STATE DEPARTMENT OF HEALTH AND THE TOWN OF NEWBURGH.
- 2. ALL WATER SERVICE LINES (4) INCHES AND LARGER IN DIAMETER SHALL BE CEMENT LINED. CLASS 52, DUCTILE IRON PIPE CONFORMING TO ANSI/AWWA C151/A21.51-91 OR LATER REVISION FOR DUCTILE IRON PIPE JOINTS SHALL BE EITHER PUSH-ON OR MECHANICAL JOINT AS REQUIRED.
- 3. THRUST RESTRAINT OF THE PIPE SHALL BE THROUGH THE USE OF JOINT RESTRAINT. THRUST BLOCKS ARE NOT ACCEPTABLE. JOINT RESTRAINT SHALL BE THROUGH THE USE OF MECHANICAL JOINT PIPE WITH RETAINER GLANDS. ALL FITTINGS AND VALVES SHALL ALSO BE INSTALLED WITH RETAINER GLANDS FOR JOINT RESTRAINT. RETAINER GLANDS SHALL BE EBBA IRON MEGALUG SERIES 1100 OR APPROVED EQUAL. THE USE OF MANUFACTURED
- RESTRAINED JOINT PIPE IS ACCEPTABLE WITH PRIOR APPROVAL OF THE WATER DEPARTMENT.

  4. ALL FITTINGS SHALL BE CAST IRON OR DUCTILE IRON, MECHANICL JOINT, CLASS 250 AND CONFORM TO ANSI/AWWA C110/A21.10-87 OR LATEST REVISION FOR DUCTILE AND GRAY IRON FITTINGS FOR ANSI/AWA C153/A21.53-94 FOR LATEST REVISION FOR DUCTILE IRON COMPACT FITTINGS.
- 5. ALL VALVES SHALL BE RESILIENT WEDGE, MECHANICAL JOINT GATE VALVES CONFORMING TO ANSI/AWWA C509 OR LATEST REVISION SUCH AS MUELLER A-2360-23 OR APPROVED EQUAL. ALL GATE VALVES SHALL OPEN LEFT (COUNTER CLOCKWISE).
- 6. TAPPING SLEEVE SHALL BE MECHANICAL JOINT SUCH AS MUELLER H-615 OR EQUAL. TAPPING VALVE SHALL BE RESILIENT WEDGE GATE VALVES CONFORMING TO ANSI/AWWA C509 SUCH AS MUELLER MODEL T-2360-19 OR APPROVED EQUAL. ALL TAPPING SLEEVES AND VALVES SHALL BE TESTED TO 150PSI MINIMUM; TESTING OF THE TAPPING SLEEVE AND VALVE MUST BE WITNESSED AND ACCEPTED BY THE TOWN OF NEWBURGH WATER DEPARTMENT PRIOR TO CUTTING INTO THE PIPE.
- 7. ALL WATER SERVICE LINES TWO (2) INCHES IN DIAMETER AND SMALLER SHALL BE TYPE K COPPER TUBING. CORPORATION STOPS SHALL BE MUELLER H-15020 FOR 3/4 AND 1 INCH, MUELLER H-15000 OR B-25000 FOR 1 1/2 OR 2 INCH SIZES. CURB VALVES SHALL BE MUELLER H-1502-2 FOR 3/4 AND 1 INCH AND MUELLER B-25204 FOR 1 1/2 AND 2 INCH SIZES. CURB BOXES SHALL BE MUELLER H-10314 FOR 3/4 AND 1 INCH AND MUELLER H-10310 FOR 1  $\frac{1}{2}$  AND 2 INCH SIZES.
- 8. ALL PIPE INSTALLATION SHALL BE SUBJECT TO INSPECTION BY THE TOWN OF NEWBURGH WATER DEPARTMENT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING ALL INSPECTIONS AS REQUIRED WITH THE TOWN OF NEWBURGH WATER DEPARTMENT.
- 9. THE WATER MAIN SHALL BE TESTED, DISINFECTED AND FLUSHED IN ACCORDANCE WITH THE TOWN OF NEWBURGH REQUIREMENTS. ALL TESTING, DISINFECTION AND FLUSHING SHALL BE COORDINATED WITH THE TOWN OF NEWBURGH WATER DEPARTMENT. PRIOR TO PUTTING THE WATER MAIN IN SERVICE, SATISFACTORY SANITARY RESULTS FROM A CERTIFIED LAB MUST BE SUBMITTED TO THE TOWN OF NEWBURGH WATER DEPARTMENT. THE TEST SAMPLES MUST BE COLLECTED BY A REPRESENTATIVE OF THE TESTING LABORATORY AND WITNESSED BY THE WATER DEPARTMENT.

#### TYPICAL <u>WATER SERVICE DETAIL</u>



# TYPICAL WATER LINE TRENCH



BACKFILL SHALL BE RUN-OF-BANK GRAVEL COMPACTED IN 6" LIFTS.

DETAIL SHEET FOR

SERVISS

TOWN OF NEWBURGH SCALE: 1"=50'

ORANGE COUNTY, N.Y.
MAY 17, 2019
REVISED: JULY 19, 2019

TOWN OF NEWBURGH PROJECT #2019-10

LIC.49087
PROPESSIONAL LAND SURVEYOR
GOSHEN, NEW YORK

UNAUTHORIZED ALTERATION OF THIS DOCUMENT, IN ANY WAY, CONSTITUTES A VIOLATION OF THE STATE OF NEW YORK EDUCATION LAW SECTION 7209 (2).